

voestalpine's Field Tests of Advanced Rail Steels

Norbert Frank
Head of Technical Customer Service

voestalpine Schienen GmbH
www.voestalpine.com

voestalpine
ONE STEP AHEAD.

Rail Field Testing at Different Conditions



voestalpine Schienen GmbH
2 | 03.02.2006 | Rail Technology/LCC Workshop

voestalpine
ONE STEP AHEAD.


Rail Damage – Requested Material Properties

curve	radius [m]	damage	requirements for rail
tight	< 700	wear	highest wear resistance
average	500 – 2000	head checks	long HC incubation period slow HC growth
wide	1500 – 6000	corrugations squats belgrospies	high yield strength long HC incubation period
tangent	> 3000	corrugations squats	high yield strength long HC incubation period

Advanced Pearlitic Rail Steels


Grade	composition	properties
R350HT	according EN13674-1 traditional HSH®-rail	approx. 370 BHN, wear rate approx. 1/3 of R260
R350LHT	according EN13674-1 HSH®-rail with Cr ~ 0,25 %	approx. 380 BHN, well established heavy haul grade of the 90s
370LHT	HSH®-rail with Cr ~ 0,50 %	390 – 400 BHN, higher wear and RCF resistance
400UHC	R350LHT with approx. 0,95 - 1,00 % Carbon – hypereutectoid rail steel	400 – 440 BHN, today highest wear resistance

Hypereutectoide Rail Steels – UHC Concept



Thicker cementite lamellae increase wear resistance

Lab testing:
10 – 20 % less wear




voestalpine Schienen GmbH

5 | 03.02.2006 | Rail Technology/LCC Workshop

voestalpine
ONE STEP AHEAD.

voestalpine's Track Tests



voestalpine Schienen GmbH


6 | 03.02.2006 | Rail Technology/LCC Workshop

voestalpine
ONE STEP AHEAD.

Track Testing at the Ofotbanan/Norway



- n Iron ore line – LKAB
- n 50 % curves with $R < 500$ m
- n 40 % declination with 20 ‰
- n Axle load 25/30 tons
- n 30 Mio t/a



voestalpine Schienen GmbH

7 | 03.02.2006 | Rail Technology/LCC Workshop

voestalpine
ONE STEP AHEAD.

Track Testing at the Ofotbanan/Norway



- n Regular rail steel:
- n S1200 micro-alloyed
- n High Wear Rates
- n Head Checks
- n Spalling

voestalpine Schienen GmbH

8 | 03.02.2006 | Rail Technology/LCC Workshop

voestalpine
ONE STEP AHEAD.

Ototbanaan – Test Conditions

- n status 1997 – Micro-alloyed S1200 best solution
 - n Test with head hardened rail steels:
 - n R350HT – 370 BHN
 - n 370LHT – 390 BHN
 - n Critical topic:
aluminothermic welds
- 




voestalpine Schienen GmbH

9 | 03.02.2006 | Rail Technology/LCC Workshop

voestalpine
ONE STEP AHEAD.

Ototbanan – Wear Measurements



voestalpine Schienen GmbH

10 | 03.02.2006 | Rail Technology/LCC Workshop

voestalpine
ONE STEP AHEAD.

Ototbanan – RCF Performance



- n R350HT – 370 BHN
 - n Head checks
 - n Spalling
 - n One year of service



- n 370LHT – 390 BHN
 - n Head checks
 - n No spalling
 - n Two years of service

voestalpine Schienen GmbH

11 | 03.02.2006 | Rail Technology/LCC Workshop

voestalpine
ONE STEP AHEAD.

Ototbanan – Weld Performance



- n Z90HC weld:
 - n Some battering
 - n Spalling next to weld




- n HPW weld:
 - n Less battering
 - n No spalling next to weld
 - n Approved!

voestalpine Schienen GmbH

12 | 03.02.2006 | Rail Technology/LCC Workshop

voestalpine
ONE STEP AHEAD.

Track Testing with US Heavy Haul



- n TTI Pueblo:
R = 350 m
110 Mio to/a
4 years
- n Union Pacific:
R = 175 – 250 m
approx. 130 Mio to/a
2 years
- n Test rails:
UHC 400 with 420 – 440 HB

voestalpine Schienen GmbH

13 | 03.02.2006 | Rail Technology/LCC Workshop

voestalpine
ONE STEP AHEAD.

Track Test with Union Pacific



- n Photo shows typical surface after one year (!)
- n Conclusions:
wear resistance of newest generation pearlitics is approx. 15 % higher compared to 400 BHN steels
all manufacturers within $\pm 5 \%$
- n New test with UP:
R = 800 – 2000 m
Focus: **RCF-performance**

voestalpine Schienen GmbH

14 | 03.02.2006 | Rail Technology/LCC Workshop

voestalpine
ONE STEP AHEAD.

Summary of the Wear Tests

- n Testing in tight curves confirm that:
- n Wear resistance increases with rail hardness:
- n R260 – HSH = 1 : 3
- n HSH – 370 LHT = 1 : 2
- n HSH – UHC 400 = 1 : 3
- n Reduced RCF-damage at higher rail hardness

RCF Study with DB AG

- n Comprehensive track testing at medium and high speed lines
- n At tight, medium and wide curves
- n Mixed traffic up to 22,5 to axle load
- n 90.000 to/day – highest daily loads available at DB
- n Monitoring, documentation and conclusions by FTZ

RCF – Crack Characterization



- n Magnetic particle inspection
- n In-Track Eddy current testing
- n Metallography of cut samples



voestalpine Schienen GmbH

19 | 03.02.2006 | Rail Technology/LCC Workshop

voestalpine
ONE STEP AHEAD.

High Speed Line Hannover-Würzburg

- n Speed up to 280 km/h
= 175 mph
- n Mixed traffic
up to 20 to/axle
- n R = tangent, 6.000 m
- n Load: 60.000 to/day
- n Rail grades:
 - n R260
 - n R350HT (HSH)
- n Track inspection and measurements
by DB-Systemtechnik at ½-years
intervals
- n Testing for 3 years



voestalpine Schienen GmbH

20 | 03.02.2006 | Rail Technology/LCC Workshop

voestalpine
ONE STEP AHEAD.

Tangent – Corrugations after 66 Mio to




- n Surfaces etched to show the White Eching Layers (WEL)
- n WEL identifies damaged material
- n Can be starter for vertical cracks

voestalpine Schienen GmbH

21 | 03.02.2006 | Rail Technology/LCC Workshop

voestalpine
ONE STEP AHEAD.

Longitudinal Profiles after 66 Mio to



voestalpine Schienen GmbH

22 | 03.02.2006 | Rail Technology/LCC Workshop

voestalpine
ONE STEP AHEAD.

Medium Speed Line München-Augsburg

- n Speeds up to 200 km/h
- n Mixed traffic
up to 22,5 to/axle
- n $R = 3.300 \text{ m}$
- n Load: 90.000 to/day
- n Three rail grades:
 - n R220 (800)
 - n R260 (900A)
 - n R350HT (HSH)
- n Track inspection and measurements
by DB-Systemtechnik at ½-years
intervals
- n Testing for 3 years




voestalpine Schienen GmbH


23 | 03.02.2006 | Rail Technology/LCC Workshop

voestalpine
ONE STEP AHEAD.

Compare: Head Checks on the Old Grade 900A Rails



- n Rail surface after 9 years
- n 300 Mio to total load
- n Grade 900A



- n Severe head checks
- n 5 mm deep (!)
- n Rail was never ground
- n Had to be replaced

voestalpine Schienen GmbH

24 | 03.02.2006 | Rail Technology/LCC Workshop

voestalpine
ONE STEP AHEAD.

Results after 3 Years – 100 Mio to




- n Wear
- n Head Checks

voestalpine Schienen GmbH

25 | 03.02.2006 | Rail Technology/LCC Workshop

voestalpine
ONE STEP AHEAD.

Wear – Cross Sectional Profiles



- n Higher hardness
- n Less wear

voestalpine Schienen GmbH

26 | 03.02.2006 | Rail Technology/LCC Workshop

voestalpine
ONE STEP AHEAD.

RCF-Defects at Three Different Grades


- n All three in the same curve
- n 800 – softer than usual
- n 900A – regular steel grade for these curves
- n HSH – head hardened rail steel



voestalpine Schienen GmbH
27 | 03.02.2006 | Rail Technology/LCC Workshop

voestalpine
ONE STEP AHEAD.

Dimensions of the Head Checked Area




grade	a [mm]	b [mm]
R220	1,7	18
R260	1,2	15
R350HT	0,8	12

voestalpine Schienen GmbH
28 | 03.02.2006 | Rail Technology/LCC Workshop

voestalpine
ONE STEP AHEAD.

Crack Depth – Eddy Current Testing





Crack depth [mm]		
grade	mean	Max.
R220	1,5	3,0
R260	1,0	1,5
R350HT	0,3	0,5

voestalpine Schienen GmbH

29 | 03.02.2006 | Rail Technology/LCC Workshop

voestalpine
ONE STEP AHEAD.

Crack Depth – Metallography



voestalpine Schienen GmbH

30 | 03.02.2006 | Rail Technology/LCC Workshop

voestalpine
ONE STEP AHEAD.

Summary of the RCF Tests

- n Testing in medium curves confirm that:
- n Wear resistance increases with rail hardness
- n Corrugation damage reduces with increasing hardness
- n Higher RCF-resistance at higher rail hardness:
- n $R220 - R260 = 1 : 1,7$
- n $R260 - R350HT = 1 : 3,2$

voestalpine Schienen GmbH
31 | 03.02.2006 | Rail Technology/LCC Workshop

voestalpine
ONE STEP AHEAD.

Bainitic Rail Steels

voestalpine Schienen GmbH
www.voestalpine.com

voestalpine
ONE STEP AHEAD.

Status of Pearlitic Rail Steels

- n Heavy Haul impossible without high strength steels
- n clean rail steels avoid detail fractures

- n high productivity
- n QA guarantees consistent high quality

- n advanced pearlitic metallurgies perform well:
 - n 370LHT – 0,5% Cr
 - n UHC400 – hypereutectoid pearlite with 1 % C

- n so why BAINITE?

Bainitic Rail Steels – Concepts


- n Carbide free Bainite:
 - n Good against RCF
 - n But low wear resistance

- n Hardened and tempered:
 - n High wear resistance
 - n But difficult to industrialize


- n Lower Bainite:
 - n Combines large wear resistance with
 - n Sufficient wear resistance

Microstructure of Pearlite and Lower Bainite

Pearlite



Bainite



voestalpine Schienen GmbH

35 | 03.02.2006 | Rail Technology/LCC Workshop

voestalpine
ONE STEP AHEAD.

DOBAIN – Pilot Hardening Plant




voestalpine Schienen GmbH

36 | 03.02.2006 | Rail Technology/LCC Workshop

voestalpine
ONE STEP AHEAD.

Properties of R260 – R350HT – DOBAIN



voestalpine Schienen GmbH

37 | 03.02.2006 | Rail Technology/LCC Workshop

voestalpine
ONE STEP AHEAD.

Semmering – Bainitic Rails

- n mountain track
- n mixed traffic
up to 22,5 to/axle
- n max. 80 km/h
- n $R = 185$ m
- n ~ 20 MGT/year

- n two DOBAIN 1 rails
compared to
premium HSH

- n Installed 1999
- n Still in track




voestalpine Schienen GmbH

38 | 03.02.2006 | Rail Technology/LCC Workshop

voestalpine
ONE STEP AHEAD.

Semmering – Typical Defects




- n Wear
- n Head Checks
- n Corrugations at the Low Rail

voestalpine Schienen GmbH

39 | 03.02.2006 | Rail Technology/LCC Workshop

voestalpine
ONE STEP AHEAD.

Semmering – Gauge Corner Wear at 60 Mio to



voestalpine Schienen GmbH

40 | 03.02.2006 | Rail Technology/LCC Workshop

voestalpine
ONE STEP AHEAD.

Semmering – RCF at 60 Mio to



- n Regular rail for Semmering
- n HSH = R350HT
- n Light Head Checks
- n Bainitic test rail
- n DOBAIN
- n No Head Checks

voestalpine Schienen GmbH

41 | 03.02.2006 | Rail Technology/LCC Workshop

voestalpine
ONE STEP AHEAD.

Semmering – Flashbutt Weld at 120 Mio to



- n Weld joins two 15 m DOBAIN rails
- n Softer than the rail
- n Battering
- n Welding needs optimization

voestalpine Schienen GmbH

42 | 03.02.2006 | Rail Technology/LCC Workshop

voestalpine
ONE STEP AHEAD.

Semmering/ÖBB – Conclusions


- n DOBAIN 1 Rails tested in wear regime
- n wear resistance close to head hardened
- n RCF resistance larger – no head checks present
- n continue testing to wear limits
- n Optimization required to improve wear resistance and weldability
- n Now more than 120 Mio to carried

voestalpine Schienen GmbH

43 | 03.02.2006 | Rail Technology/LCC Workshop

voestalpine
ONE STEP AHEAD.

Wear of Bainitic Rail Steels



voestalpine Schienen GmbH

44 | 03.02.2006 | Rail Technology/LCC Workshop

voestalpine
ONE STEP AHEAD.

DOBAIN 2 – Optimization Steps

- n Adjust chemical composition to higher C-levels
- n Adjust heat treatment to appropriate hardness
- n DOBAIN 430: heavy haul, mixed traffic
- n DOBAIN 380: mixed traffic, high speed, Metro
- n DOBAIN 340: high speed, low axle loads
- n Goal: no RCF, adjust wear rates acc. to loads

voestalpine Schienen GmbH

45 | 03.02.2006 | Rail Technology/LCC Workshop

voestalpine
ONE STEP AHEAD.

Medium Speed Line München-Augsburg

- n Same curve, other direction used
- n Similar installation like first test
- n Now four rail grades in test:
 - n R260 Pearlite
 - n R350HT HSH
 - n 370LHT Pearlite
 - n DOBAIN 430 Bainite




voestalpine Schienen GmbH

46 | 03.02.2006 | Rail Technology/LCC Workshop

voestalpine
ONE STEP AHEAD.

Preliminary MPI Results for Medium Speed Line



Bainitic Rail Steels – Summary

- n Wear properties similar to HSH – sufficient for EU conditions
- n RCF:
 - n Much better than R260
 - n better than HSH
 - n comparable to high end pearlites – to be verified in current tests
- n Continue with all tests:
 - n Semmering: mixed traffic in tightest radii
 - n Rheinbraun/FRG: heavy haul conditions
 - n DB AG: three test at low, medium and wide radii
- n Welding must be optimized – cooperations with ET and VAE
- n Start new tests!

Steel Grade Impact on Maintenance Strategy and Costs

voestalpine Schienen GmbH
www.voestalpine.com

voestalpine
ONE STEP AHEAD.


voestalpine's Track Tests

- n Tests are done with different customers
 - n at different load conditions
 - n on different levels of maintenance capabilities
 - n with different rolling stock
 - n in open (revenue) or closed (TTCI, ore-lines) systems
 - n ...
- n Not all tests are done on the same level of sophistication (DB AG)
- n See summary of Wear results
- n See summary on Head Checking

voestalpine Schienen GmbH
50 | 03.02.2006 | Rail Technology/LCC Workshop

voestalpine
ONE STEP AHEAD.

Track Test Results – Gauge Corner Wear



n Advanced rail steels drop wear rates significantly


n Wear is the primary replacement criterium in tight curves below 500 m radius

voestalpine Schienen GmbH

51 | 03.02.2006 | Rail Technology/LCC Workshop

voestalpine
ONE STEP AHEAD.

Track Test Results – Head Checking



n Advanced rail steels reduce Head Check depth significantly

n RCF primary problem for curves larger than 700 m

n Grinding required

voestalpine Schienen GmbH

52 | 03.02.2006 | Rail Technology/LCC Workshop

voestalpine
ONE STEP AHEAD.

Maintenance Strategy


- n Wear – clear answer:
 - n use the hardest rail steel available – see Heavy Hauling
- n Rolling Contact Fatigue – case dependent:
 - n Grinding to remove the cracks
 - n Preventive grinding
 - n Corrective grinding
 - n Repair welding of localized defects
 - n Rail replacement

voestalpine Schienen GmbH

53 | 03.02.2006 | Rail Technology/LCC Workshop

voestalpine
ONE STEP AHEAD.

Maintenance – The Magic Wear Rate



source: J. Kalousek and E. Magel: The "Magic" Wear Rate
RT&S March 1997, pp.50-52

voestalpine Schienen GmbH

54 | 03.02.2006 | Rail Technology/LCC Workshop

voestalpine
ONE STEP AHEAD.

Medium Speed Line München-Augsburg

- n R = 3.300 m
- n Load: 90.000 to/day
- n Three rail grades:
 - n R220 (800)
 - n R260 (900A)
 - n R350HT (HSH®)
- n Testing for 3 years

- n Grinding tests:
determine material removal
required for a defect-free
surface



voestalpine Schienen GmbH

55 | 03.02.2006 | Rail Technology/LCC Workshop

voestalpine
ONE STEP AHEAD.

Grinding Tests – Head Check Removal

grade	no. grinding passes	material removal	result
R220	22	2,6 mm	continuous head checks
R260	12	0,8 mm	sporadic head checks
R350HT	6	0,6 mm	clean surface

voestalpine Schienen GmbH

56 | 03.02.2006 | Rail Technology/LCC Workshop

voestalpine
ONE STEP AHEAD.


Grinding Tests – Life Cycle Prognosis

grade	Material loss [mm]	Expected service life	+/-
R220	3,5	6,6	- 60 %
R260	1,4	16,4	reference
R350HT	1,0	23	+ 40 %

Summary on R350HT vs. R260

- n less corrugations:
 - n 1/3 roughness and 1/2 wavelength
- n approx. 40 % less wear
- n Head Checks finer and shorter
- n later crack initiation and slower crack growth
- n 70 % lower crack depth
- n only half of the grinding passes required
- n 40 % increased service time

Rail Grade Strategy – Status 2006




voestalpine Schienen GmbH

59 | 03.02.2006 | Rail Technology/LCC Workshop

voestalpine
ONE STEP AHEAD.

Rail Grade Strategy – Recommendation 2006



voestalpine Schienen GmbH

60 | 03.02.2006 | Rail Technology/LCC Workshop

voestalpine
ONE STEP AHEAD.